

# SUNGROW

## CHANNEL PRODUCT & SOLUTION INTRODUCTION



# Contents

---

1. C&I Products Introduction
2. Comparison with Other Brand
3. Optimizer & RSD Solution Highlights



## SG 33-40-50 / 125 CX-P2

### Max. PV input voltage

1100V

### No. of independent MPP inputs

3 / 4 / 4 / 12

### Max. PV input current

90 / 120 / 120 / 360 A

### Max. AC output apparent power

36.3 / 44 / 55 / 125kVA

### Surge protection

DC Type I+II / AC Type II

### PV String current monitoring

### Arc fault circuit interrupter (AFCI)

### PID recovery function

### Global MPP Tracking

### 10s live data refresh

### String level IV Curve Scanning

### Patent Structural Design

### Water and dust resistance

IP66

### Corrosion resistance

C5

### Operating ambient temperature

### range

-30 to 60 °C

# COMMUNICATION DEVICES

SUNGROW



	Winet-S	COM100E
No. of access devices	1	≤30
Automatic device search and setup	✓	✓
QR code for automatic cloud connection	✓	✓
O&M remotely and locally	✓	✓
Build-in WEB server	✓	✓
<b>Zero export function</b>	✓	✓
<b>Support of data Transfer via FTP</b>	✓	✓
<b>API to 3<sup>rd</sup>-party monitoring platform</b>	✓	✓
Weather station		✓


# PID Recovery Reduces Modules From Performance Degradation

The system boosts PV-to-ground voltage to recover modules degradation, always keep the best performance of PV modules.

## Experiments verify that

Boosting PV-to-ground voltage can repair module damage caused by PID

▲ 8.8%




# Global MPPT Tracking Increase Generation by 2%

The MPPT's can identify the global MPP and maximize the yield of your PV plant in case of shading.

Full-curve scanning allows for precise tracking of the maximum power point (P4)




For the traditional scheme, local peak power point (P1) may be misidentified as the global peak



# AFCI Protection Performance


Far Outperforms That Required by UL1699B, reducing the electrical accidents caused by DC arc faults, guarding the safety at all times.



\* All the performances apply to the SOLUTIONs with or without PV module optimizers.  
Note: Typical values from experimental test data

## String-level Locating

Help to position the string where an arc fault occurs.



# SPD Protection



## Industry's First DC I/II Lightning Protection Inverter

Effective protection for direct and indirect lightening strike

Lightning Protection	CX-P2	Discharge Capacity	Waveform
• DC I+ II SPD	✓	20KA	10/350us 8/20uS
• AC II SPD	✓	20KA	8/20uS
• Communication IV SPD	✓	6KA	8/20uS

# Patent Structural Design, Saving Operation Time



Dedicated installation methods are designed for models of different power segments to reduce the installation time by up to 30%.

## Side handles

With 4 detachable side handles for easy lifting and handling of the inverter.

## New AC cabinet


Connectors are easily accessible and positioned at the perfect height.

## Door stopper

Practical door stop to keep the AC compartment open during installation or maintenance.

## AC sealing plate

Adaptive sealing plate to cable diameter.



## Smart String IV Curve Scanning

SUNGROW's intelligent IV curve analysis technology owns dual certification from TÜV and CGC, reaching **the industry's highest Level 4 rating**

**< 1s**  
Reaction  
Single  
String

**>17**  
Types of faults  
analyzation

**≥ 90%**  
Scanning  
Accuracy

**≥ 95%**  
Precise Judgment  
Accuracy

# Contents

---


1. C&I Products Introduction
2. Comparison with Other Brand
3. Optimizer & RSD Solution Highlights

# Wider MPP Voltage Range, Longer Serving Time


SUNGROW

Start-up input voltage 200V / MPP voltage range 160-1000V


## 1 SG25-50CX-P2 power range



## 2 SG125CX-P2 power range




Start Earlier And Stop Later



# Power-DC Input Voltage Curve Comparison


SUNGROW




400V grid voltage, SG125CX-P2 with wider Voltage range while Full-load output for flexible design and control voltage drop rate.

# Temperature De-rating Curve Comparison

SG125CX-P2 @ 600V



100kW inverter @ 600V



If designed with 600V DC input, SUNGROW SG125CX-P2 will start derating output when the ambient temperature above 45°C. While other brand 100kW inverter will start derating output when the ambient temperature above 30°C.

## Test Procedure

### DEVICE SETTING.

- ① Turn off the inverter.
- ② Connect the arc simulator in series with the PV string and the inverter.



### OPERATION.

- ④ Turn on the inverter again and wait for inverter connect to grid and run normally.

### CONNECTION.

- ③ Connect the current and voltage sensors of oscilloscope to one of DC string and arc simulator.

The kit following IEC63027 and UL1699B standards can eliminate the influence of human factors and limit the factors to DC cable length and current.





### SIMULATING TEST.

- ⑤ Send command to arc simulator via laptop to simulate the arc fault follow the standard.
- ⑥ Check and confirm inverter has been stop and display AFCI alarm.

### MONITORING & CONTROL.

- ⑦ Check and confirm inverter has been stop and display AFCI alarm.
- ⑧ Check and record tripping time and waveform.



No.	String No.	Cable Length	DC Current	Test No.	Pass No.	Result
1	String 1	<u>178 m</u>	7.5 A	2	2	100%
2	String 5	<u>234 m</u>	7.8 A	2	2	100%
3	String 11	<u>297 m</u>	7.6 A	2	2	100%
4	String 20	<u>412 m</u>	7.4 A	2	2	100%

## **Site test: SG125CX-P2**

# Other Performance Comparison

SUNGROW


ITEM	SUNGROW	Other Brand	Mark
DC Connector	30A , EVO2	/ , MC4	complies to higher voltage standard
SPD Design	Type I+II	Type II	better surge power protection for PV side
Data Refresh	10s	5min	quicker commissioning and efficient maintenance
Optimizer Solution	SG125CX-P2	50kW	Low BOS cost
Arc String locating	support	No support	Easy for maintenance

# Contents

---

1. C&I Products Introduction
2. Comparison with Other Brand
3. Optimizer & RSD Solution Highlights

# System Rapid Shutdown Solutions




# One-brand & High-integrated System

One-brand system with monitoring full support from SUNGROW

Highly integrated system without external control box easy for design and commissioning

Patented FHC bypass & Active safety (AFCI + Rapid Shutdown)

PLC distance  $\leq 350$  m



# Tool Free Installation Save 45% Installation Time

SUNGROW

## SUNGROW Solution

only takes **35s** to finish installation



Border clamp **5s**

Cable connection **30s**

Patented Design



## Other Brand Solution

Installation time **> 1min**




**TUV Rheinland verified the reliability of the quick-plug**

TUV Rheinland verified the reliability of the quick-plug			
8.5	Wall mounting	Mounting brackets withstand a force of four times the weight of the equipment.	P

# Saving Installation Time & Resource

SUNGROW


## *Traditional Installation*



*Mounting optimizer with rail*

**Support optimizer pre-mounting with PV panel on ground, reduce and operation on rooftop.**

## *SUNGROW Installation*



*Mounting optimizer with PV panel frame*



# Saving 4 Times Maintenance Resource

---


SUNGROW

Traditional maintenance



VS

Quick plug installation and maintenance




4 person, remove panel first then replace faulty optimizer

1 person, replace faulty optimizer directly

# Patented Active Bypass / Smart and Reliable

Normally, the control switch is on and gets power from 2 PV modules and outputs power to other series SR20D-M.



## Bypass Mode

In the case of communication issue, module fault or RSD fault, the RSD will enter **bypass mode** and not affect other modules in this string.

### Smart


- ✓ Actively status detection
- ✓ Active shading identification
- ✓ Active on-demand bypass

### Reliable

- ✓ Lower heat
- ✓ Lower power consumption
- ✓ More reliable, longer lifetime

## Comparison with 3rd RSD

SUNGROW has self-developed chip inside SR20D-M that control temperature 60 °C to 70 °C lower than 3rd RSD.




If 3rd RSD works in bypass mode, the temperature will exceed the *Upper limit of component temperature then lead to high fault rate*.

# AFCI+RSD

## / Dual Protection & Active safety


Only the AFCI function is combined with RSD, the active safety of the system can be ensured.

The inverter actively detects a true arc and will automatically shutdown, meanwhile the RSD will quickly shutdown the system. Then the fault detection can be carried out in time.




Help to position the string where an arc fault occurs

Shutdown time	0.2 s - 1.5 s	Cable length	200 m	MPPT current	32 A
---------------	---------------	--------------	-------	--------------	------



Note: Typical values from experimental test data  
 \*All the performances apply to the SOLUTIONs with or without PV module optimizers.

Shutdown time	<20s	Safe voltage	1V
---------------	------	--------------	----



Shutdown within 20 s, much shorter than required by NEC standard

**Module-level fault positioning**

Optimizer 5-3-13	
S/N:	A22B0205121
Tilt Angle:	0
Azimuth Angle:	0
Data Update Time: 2024-01-23 13:20	
Total Yield	91.374 kWh
Input Voltage	37.8 V
Output Voltage	37.4 V
Input Current	3.9 A
Output Current	3.91 A
Output Power	146.5 W
Device Name: Optimizer	
Commissioning Date: 2023-12-08 14:30:24	
Module Model: --	
S/N: A22B0205121	
Module Manufacturer: --	
Settings	


# About our Monitoring Platform

iSolarCloud supports PV panels **virtual layout 100% matching with installation layout**, different color indicates different operation states and supporting location faulty panel obviously.  
It also provides comprehensive monitoring to check the status of each unit like output power/voltage/current.

## String-level IV Diagnosis

For RSD

<b>&lt; 1s</b>	<b>&gt; 17</b>
Reaction Single String	Types of faults analyzation



## Module-level IV Diagnosis

For Optimizer

<b>≥ 90%</b>	<b>≥ 95%</b>
Scanning Accuracy	Precise Judgment Accuracy

\* Enable IV Curve scan when the sky is sunny without cloud.

\*\* The monitoring system needs to be equipped with Sungrow logger and iSolarCloud.



# THANKS

